
Product Components and Specification



| Category | Product Specification | | | | | | |
|--|--|---|--------------------------------|------------|---------------|----------------|--|
| Rated Voltage | AA Type Alkaline 1,5V Battery (LR6) 8pcs (12V) | | | | | | |
| Emergency Power | 9V Battery (6LF22) 1pcs (Purchased Separately) | | | | | | |
| Operation Type | Electronic Control System (Face Recognition, Password, Card) | | | | | | |
| Weight | | 2,95kg (Exterior and Interior Parts Included) | | | | | |
| Product Size | Interior | | 84mm(W) X 363,5mm(H) X 69mm(D) | | | | |
| | Exterior | | 85mm(W) X 367mm(H) X 73mm(D) | | | | |
| Category | | RF | RF Type | RF Type | RF Type | Operation Type | |
| RFID | 13,56MHz Range | | A1D | ASK | Single Typ | oe . | |
| Safety System Type | 447,275MHz | | F1D | FSK | Single Typ | ре | |
| Certificate of Free Safety Check Number | | B223H006-6003 | | | | | |
| Type and Symbol | | F-T-K-M | | | | | |
| Certification Number | | R-R-iRY-IFP-7070 | | | | | |
| Model H-7070 | | | | | | | |
| Developer · Seller Hione Plus | | | s | | | | |
| Manufacturer Hione Plu | | s | Country of | f Origin N | Made in Korea | | |
| Date of Manufacture | | | | | | | |

1. How to open door

1) Door Opening (Face Registration)



- Press power button.
 Place your face to fit into the screen for face authentication.



If a part of the face is covered with a hat, glasses, sunglasses, or eyeglasses, the authentication may fail,

2) Door Opening (Password)



- Press the power button.
 After pressing the "key icon," press the touch screen to insert the registered password.
 Press the OK button to open the door.


Entering wrong password for 5 times will activate forced suspension of the use for 7 seconds and automatically capture the image of the user in front,

3) Door Opening (Card Key)



1. Make the card key contact the card sensing area for authentication,

4) Door Opening (Emergency Key)



- Activate the keypad by pressing start button,
 Press the set password, then press start button to open the door,

Entering error of the emergency keypad for 3 times will activate forced suspension of the external button control and sound the alarm,

Intelligent Door-lock System with Face Recognition Technology

Face Recognition Door-lock **User Manual**

For the product with the emergency key applied, the emergency key must be carried in a wallet, handbag etc., or stored in a sale place outside of home (Car etc.,) to be used safely.



- InT Service (Optional)
 Door can be unlocked through the loT service from inside.
- Password, Card (NFC Function) assword and card can be conveniently sed and are freely set and changed.
 - Fire Sensor Function
 In case of fire, detection of temperature
 above 65°C will activate the door to open
 for easy escape.
- Up to 100 Passwords Registration Function 100 users can use each different passwords.
- Automatic Locking Time
 Setting Function
 After the door closes, the automatic locking time can be freely set,

"The instruction of emergency manual opening and closing of the device must be well-acquainted with," "This product is key type/non-key type door-lock and parts of the door-lock can be broken to open incase of malfunctions."

2. Required Settings (Re-setting after Factory Default)

1) Administrator Mode



- * During the initial operation after the installation of the door-lock, register at least one security setting.
- 1, Master PWD: Choose password and register 6 to 8 digits numbers,
- 2. Master Card: Choose master card and contact the card sensor with the card

3. How to Use

1) Administrator Mode



- ** Master password is the compulsory setting that must be registered in the initial operation and it can be set/changed in 'Menu' > Setting'.
- 1. Press the home icon button after turning on the power,

2-1) Face Registration





- Press 'User' > 'Add User' > 'Face Regist,' button.
 Move your face to fit all areas of the face into the screen and wait until the loading of the green bar at the bottom is completed.

- 1, Please keep the distance between the face and door-lock to be 40~80cm 2, Please do not wear hals, glasses, sunglasses, eve patch and etc., 3. Be cautious to make sure only one person appears on the screen when registering, 4. Be cautious to keep the eyes at the front and not to change the facial expression





2) User Registration






- 1. Press 'Menu' > 'User' button,
- 2. Press 'Add User' button
- * When registering a user for the first time or changing the user information, please do so with the door open having the emergency key and card handy to prevent lock out by mistake.

After registering the user, check if the door opens with the registered method.

2-2) Hand Registration




- Press 'User' > 'Add User' > 'Hand Regist.' button.
 After placing the hand to fit into the screen, wait until the loading of the green bar is completed.
- * When registering a hand, open your palm so that the fingers are distanced away from each other as shown in the figure.

2) Emergency Password Setting







- * Emergency Password Setting (Default: 1234 Must be re-set after the installation)
- 1. With the door open, open the interior battery cover and press ①button at the
- 2. Press the wanted number (Available to register 6 \sim 12 digits) at the front keypad. 3. Pressing emergency key button will make the sound and setting is completed.
- 4. Please proceed to setting 1,2,3 above once more,
- * Please register the emergency password setting twice to complete the change,

3. How to Use

2-3) Password Registration



- 1. Press 'User' > 'Add User' > 'PWD Regist,' button,
 2. After pressing the same password twice, press 'OK' button to register,

- Please assign password to be 8 to 8 digits numbers.

 The same spaceword to the administers and users are not registered.

 The passwords are not changeable after the registration.

 The passwords are not changeable after the registration.

 The user must register the password in instand on case of the Initial Installation,

 Please be noted that the incidents occurring due to the registration of the password by someone other than the user will not be half responsible by the manufacturer.

2-4) Card Registration



- Press 'User' > 'Add User' > 'Card Regist' button
 Make the card contact the card sensing area,
- * NFC function is only available for users with Android mobile device with NFC function and NFC USIM Chip..

3) User Information Deletion



- * After the registration of the user, only the administrator will be allowed to delete user information,

4) User List



- Press 'Home Icon' button > Press 'User' button.
 Press 'User List' button,
 Press the ID of interest to check the information.

5) Setting



- * Press the 'Home Button' > 'Setting' Button,
- : Chooses the language to be used in the device, 1, Language
- Sets the Volume of the device,
 After pressing the 'OK' button, the volume is reflected,
 (Initial Set-up: level 3)

3. Auto Lock Time: Sets the time of door being open in unit of seconds, (Initial set-up: 3 seconds)

: Sets the authentication type, (Refer to 5-1)

5. Battery Type : Sets the battery type of the device (Standard: Li-lon 7,4v) *Do not change the setting.

6 Time Setting : Sets the present time/date which will be displayed in the

7. Delete all users: Deletes all users' registered information. (Refer to 5-2)

8. Delete All Log $\,$: Deletes all log history of the device, (Refer to 5-3) Default Setting : All settings are returned back to factory default settings. (Refer to 5-4)

5-1) Setting-Authentication Type



- 1. Press the 'Setting' > "Authen, Type" button, 2, Sets the door opening type,

- Any
 : Any of the registered method for authentication can be used,
 Card+Face
 : Card and face both must be presented for authentication,
 Card+Hand
 : Card and hand both must be presented for authentication,

5-2) Delete All Users



- Setting > Press the "Delete All Users" button.
 Deletes all users' registered information.



- When all users' information are deleted, the administrator's authority is also deleted.
- After deleting all users' information, the administrator's authority must be re-set.

5-3) Delete All Log



- 1, Setting > Press "Delete All Log" button 2, Deletes all access log history of the device

5-4) Default Setting



- Setting > Press the "Default Setting" button.
 The device is returned back to the factory default setting.



When factory default is implemented, the administrator's authority is deleted.
 All user information (face, hand, password, card) is deleted.
 Settings back to default.

6) Security



- * Security setting is used when the menu is entered,

7) Device




- Press the 'Menu' > 'Device' button,
 The version information of the device and recorded history can be searched,

8) View Log




- Press the 'Menu' > 'Device' > 'View Log' button.
 Search period can be chosen to search the record during the specific

9) Using the Keypad




- With the door open, press 'Open/Close' button for 3 seconds, then press the number applicable,
- umber 1: Automatic/Manual Locking (Default: Automatic Locking)
 Automatic Locking Setting Three syllable sound signals the setting of the function,
 Manual Locking Setting Two syllable sounds signals the setting of the function,
- umber 2: Scrambling Password/Actual Password (Default: Actual Password Input Mode)
 Scrambling Password Setting Three syllable sound signals the setting of the function
 Actual Password Setting Two syllable sound signals the setting of the function,
- umber 4 : Automatic Locking Time Setting (Default : 2 seconds)
 Press number 4 for 1 second and press any number from 1, 2, 3, 4
 (1 : 2 seconds, 2 : 4 seconds, 3 : 6 seconds, 4 : 8 seconds)
 Ex) 4 seconds setting: Press open button for 3 seconds + Button 4 + Button 2
- ** This device is a domestic electromagnetic wave adaptor that is recommended to be used in households, ** The contents of this user manual can be edited without prior consent for the improvement of product functions, (Additional model is indicated with stickers)

10) How to open door (Interior)




- 1. Press Open/Close button or push the inside handle outwards to open the door,
- 11) Battery Replacement



1,5V "AA" 8pcs are used

- 1. Maximum usable battery times: Over 4000 times (Alkaline Battery Standard)
- Notification of battery replacement: When the alarm sounds (a melody), immediately open the interior battery cover to replace all batteries at once by appropriately litting the 1.50" AA" batteries in right +/- terminal, and do not mix use the new batteries and used batteries.

12) Emergency Power Supply



- ** This method is used when the door-lock has no power and after going inside with the emergency power supply, replace all 8pcs of 1,5V "AA" battery at once.